

ImagePerfect[™] 2830-100 Clear Gloss PWF Laminate

ImagePerfect™ 2830-100 is a laminate with a permanent, solvent-based adhesive system that has been specifically designed for protecting digital prints on perforated window films (PWF's).

ImagePerfect™ 2830-100 is a laminate that is recommended for use on perforated window films (PWF's). It has an ultra clear surface that does not obstruct the view through the PWF. It is equipped with a special, 2-component adhesive system that is resistant to moisture and it should only be dry applied (it is not compatible with wet application). When installing a PWF, it should be applied approximately 6mm from the edge of the window. The laminate should be applied over the perforated window film, leaving a gap of 1mm from the edge of the window. This then leaves an overlap of 5mm to enhance process security. This laminate can be used on IP 2701, IP 2703, IP 2706, IP 2706R and IP 2707.

Specifications	
Description	PWF laminate
Colour	Clear gloss
Thickness	70mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	12N/25mm (Finat TM 1/24h)
Release Paper	Polyester, 36mym
Temperature Range	-50°C to +110°C
Durability (unprinted)	8 years
Flame Retardancy	N/A
Shelf Life	2 years, 20°C / 50% humidity

[©] May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom